

COLPARISON - OLIVER OC-12 DIESEL LOADER VS. COMPETITION

	OLIVER OC-126	A-C HD-6G "Tip Back"	I-H TD-9-422 9K-3 Drott	Cat #955
LOADER:				
Bucket Width (in.)	80	76	78	80
Bucket Capacity (cu. yd.)	1½	1½	1½	1½
Tilt Back at Ground Line (deg.)	42	25	40	40
Tilt Back at Maximum Lift (deg.)	53	60	40	47½
Dumping Reach at Max. Height (in.) (Bucket Dumped)	34½	31 (1)	N.A.	38-3/4 (1)
Maximum Dumping Angle at Max. Lift (deg.)	45	47	61	50
Dumping Height-Center Hinge Pin to Ground (in.)	124½	120	126	128
Dumping Clearance (in.)	92½ (2)	94	96	99-3/4
Digging Depth Below Ground Line (in.)	35	13	12	12½
Hydraulic System Capacity (gals.)	N.A.	26	23	27½
Pump Capacity (GPM)	37	39	30	43
P.S.I.	1200	1000	1000	1000
R.P.M.	1700	1800	1200	1800
TRACTOR:				
Drawbar Horsepower	53.05	45	54.5	50
Governed R.P.M.	1750	1800	1550	1800
R.P.M. @ Maximum Torque	1200	1200	1100	1300

GUIDE: N.A. - Not Available

(1) At 45 degree angle - dumping reach would decrease with bucket at full dump.  
 (2) At 45 degree angle.

COMPARISON - OLIVER OC-12 DIESEL TRACTOR VS. COMPETITION

Page

OLIVER OC-126	A-C HD-6G "Tip Back"	I-H TD-9-424 9K-3 Drott	CAT #955
------------------	----------------------------	-------------------------------	-------------

TRAVEL SPEEDS AT RATED ENGINE SPEED:

First	1.60	1.5	1.5	1.7
Second	2.34	2.4	2.2	2.4
Third	3.34	3.3	3.9	3.5
Fourth	5.27	5.5	5.3	6.9
Low Reverse	1.72	2.0	1.7	1.9
High Reverse	3.60	4.1	3.5	3.0

Gauge (Center to Center of Tracks - in.)

60	60	60
----	----	----

No. Lower Track Wheels

5	6	5	5
---	---	---	---

No. Upper Track Wheels

2	1	2	1
---	---	---	---

Length of Track on Ground (in.)

71-1/16	83-3/16	72-15/16	83
---------	---------	----------	----

Width of Track Shoes (in.)

13	13	15	15
----	----	----	----

No. of Track Shoes, each side

33	39	36	38
----	----	----	----

Area Ground Contact with above Shoes(sq.in.)

1844	2163	2177	2486
------	------	------	------

Turning Radius (in.)

50 (3)	N.A.	N.A.	N.A.
--------	------	------	------

Weight - Tractor and Loader (lbs.)

16,900	19,600	18,860	21,480
--------	--------	--------	--------

EST PRICE: Tractor

\$8,436.00	\$13,800.00	\$8,862.00	\$14,599.50
------------	-------------	------------	-------------

Loader

\$3,489.50	(included)	\$4,480.00	(included)
------------	------------	------------	------------

Counterweight

220.00	N.R.	S	N.R.
--------	------	---	------

Lights

43.00	S	S	226.00
-------	---	---	--------

Mounting

125.00	(included)	145.00	(included)
--------	------------	--------	------------

Inbound Freight

140.23	(included)	46.20	(include)
--------	------------	-------	-----------

Lower Track Wheel Guards

S	S	141.00	S
---	---	--------	---

Crankcase Guard

S	S	S	S
---	---	---	---

TOTAL

\$12,453.73	\$13,800.00	\$13,674.20	\$14,825.00
-------------	-------------	-------------	-------------

GUIDE: N.A. - Not Available N.R. - Not Required S - Standard  
 (1) At 45 degree angle - Dumping reach would decrease with bucket at full dump; (2) At 45 degree dumping angle; (3) OC-12 with Power Turn, turning radius is 25"

R.F. Hama 1/3/57  
 (Replace 11-15-55)